



SINGLE PHASE AMMETER

KEY FEATURES

- Aesthetic Design
- Programmable CT ratio
- Password protection
- Continuous monitoring
- Highly accurate
- Long life

OVERALL DIMENSIONS

- Height: 48mm
- Width: 96mm
- Depth: 75mm

CUTOUT

92mm



FOR QUERIES

Visit us:

www.alindrelays.com

OR

Mail us:

contact@alindrelays.com

OR

Call us:

+91 944 600 5703



- Microcontroller Based Design suitable for all panels
- 4 digit bright LED Display for better visual indication
- Highly Durable & operates on wide range of power supplies
- True RMS value continuous and accurate measurement.

TECHNICAL SPECIFICATIONS

- ☆ Auxiliary Supply Range : 55-250V AC/DC
- ☆ Frequency : 45Hz to 55Hz
- ☆ CT Primary set range : 0 to 9999A
- ☆ CT Secondary set range, In : 1/5A
- ☆ Accuracy : +/- 0.5% of full scale reading (± 2 digit)
- ☆ Overload indication : Provided (Above 200% of nominal value)
- ☆ Display Range : 0000 - 9999
- ☆ Short time overload capacity : 20In for 3sec
- ☆ Dielectric strength : 2Mohms