



### KEY FEATURES

- Aesthetic Design
- Programmable PT ratio
- Password protection
- Continuous monitoring
- Highly accurate
- Long life

### OVERALL DIMENSIONS

- Height: 48mm
- Width: 96mm
- Depth: 75mm

### CUTOUT

92mm



### FOR QUERIES

Visit us:

[www.alindrelays.com](http://www.alindrelays.com)

OR

Mail us:

[contact@alindrelays.com](mailto:contact@alindrelays.com)

OR

Call us:

+91 944 600 5703

## SINGLE PHASE VOLTMETER



- Microcontroller Based Design suitable for all panels
- 4 digit bright LED Display for better visual indication
- Highly Durable & operates on wide range of power supplies
- True RMS value continuous and accurate measurement.

## TECHNICAL SPECIFICATIONS

- ☆ Auxiliary Supply Range : 55-250V AC/DC
- ☆ Frequency : 45Hz to 55Hz
- ☆ PT Primary set range : 0 to 9999KV
- ☆ PT Secondary set range,  $V_n$  : 60V to 240V
- ☆ Accuracy : +/- 0.5% of full scale reading ( $\pm 2$  digit)
- ☆ Overload Indication: Above 300V
- ☆ Display Range : 0000 - 9999
- ☆ Dielectric strength : 2Mohms